

NIMBUS is a stand-alone linear LED solution designed for direct ceiling mounting or suspended installation. It delivers outstanding luminous efficiency, visual comfort, and glare control, with mono-directional (down) or bi-directional (up & down) light emission. Its elegant and minimal design makes it ideal for offices, showrooms, workspaces, and commercial display areas.

Technical specifications:

- **Body:** anodized and painted extruded aluminum
- **Diffuser:** UV-resistant opal and microprismatic PMMA
- **LED modules:** ultra-efficient, powered at 200mA and 350mA
- **Color temperature:** 3000K / 4000K
- **Color rendering index:** CRI >80 (CRI >90 on request)
- **Lumen maintenance:** 80,000h L80B10 @ta25 / 50,000h L80B20 @tamax
- **Power supply:** driver 220–240V, 50/60Hz, ripple free, SP system (overload and short-circuit protection), active PFC
- **Ceiling mounting kit:** standard with 2 steel clips
- **Protection class:** Class I, IK05, IP43
- **Control:** DALI and Bluetooth ready
- **Environmental compliance:** suitable for CAM projects
- **Available customizations:**
 - Body color: white, black, others on request
 - Grids: black, white, translucent
 - Suspension kit: available on request
- **Luminous flux:**
 - Mono-directional version: from 3500lm – 18W @200mA up to 11900lm – 64W @350mA
 - Bi-directional version: from 2450lm down / 660lm up – 23W @200mA up to 11900lm down / 2070lm up – 75W @350mA